


New!



WeatherLock® Specialty Tile & Metal Waterproofing Barrier



Withstands temperatures up to 260°F without fusing or degrading overlying metal roofing. Approved for use under all metal roof systems, including copper and zinc.



Excellent surface for foam adhesive set and mechanically fastened roof tile applications.

Essential Weatherproofing Barrier.

Tile and metal shingles are water-shedding not waterproofing barriers. WeatherLock® Specialty Tile & Metal underlayment provides the weatherproofing protection your home needs to help prevent leaks. Unlike felt underlayment, *WeatherLock* Specialty Tile & Metal underlayment will not melt, tear or degrade when exposed to moisture, severe heat or cold weather.

Extended UV exposure—Resists UV degradation when left exposed for up to 90 days.

Waterproofing barrier—Adheres to roof deck and seals around nails for dependable, water-tight construction.*

Peak performance—High puncture and tear-resistant surface.

Safe installation—Single-layer polyester walking surface provides a slip-resistant work area.

30-year limited warranty—Since tile and metal shingles are water-shedding not waterproofing, rely on *WeatherLock* underlayment to provide a long-lasting roof system.**

* See installation instructions for complete details, limitations and requirements.
** See actual warranty for complete details, limitations and requirements.





The essentials for a healthy roofing system.

It takes more than just shingles to create a high-performance roof. It requires a system of products working together. Owens Corning™ Roofing Essentials™ Accessory Products work with our shingles to make up a roofing system that helps provide maximum durability for your roof. And the most protection for your home.

- a** VentSure® Ventilation Products
- b** PINK Fiberglas™ Blown-In Insulation
- c** Owens Corning™ Hip & Ridge Shingles
- d** Owens Corning™ Shingles
- e** Owens Corning™ Felt Underlayment Products
- f** WeatherLock® Self-Sealing Ice & Water Barrier Products
- g** Owens Corning™ Starter Shingle Products
- h** RapidFlow™ Gutter Drainage Protection
- i** Undereave Ventilation Products



**OWENS CORNING
ROOFING AND ASPHALT, LLC**
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659

1-800-GET-PINK™
www.roofing.owenscorning.com

Pub. No. 10011679. Printed in U.S.A. November 2009.
THE PINK PANTHER™ & © 1964–2009 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. ©2009 Owens Corning.

(Atlanta, Brookville, Denver, Kearny, Medina, Portland, Savannah and Summit)



Construction

Surface

Polyester non-woven fabric. Comprised of more than 80% recycled materials

Interior Reinforcement

Durable Fiberglas® Mat

Adhesive Styrene

Rubberized asphalt adhesive

Removable Backing

Split, silicone release poly

Typical Values†

Property	2 sq. roll
Length	66.7 ft. (20.33 m)
Width	3 ft. (.91 m)
Gross Coverage	200 sq. ft. (18.58 m ²)

Applicable Standards and Codes

ICC ESR 1783

ASTM D 1970

UL Class A, Class C

Florida Building Code

Miami-Dade County Approved

Physical Properties

Property	Test Method	Typical Values†
Thickness	—	65 mils
Slip Resistance	ASTM D 1970	Passed
Pliability	1" Mandrel Bent at -20°F	Passed
Tensile Strength	ASTM D 2523	—
Longitudinal (md)	—	86 lbs./in.
Transverse (cd)	—	59 lbs./in.
Elongation at Break (modified bitumen portion)	ASTM D 2523	250%
Permeance	ASTM E 96	.08 max
Adhesion to Plywood, 40°F	ASTM D 903	4.0 lbs./in.
Adhesion to Plywood, 75°F	ASTM D 903	2.0 lbs./in.
Tear Resistance	ASTM D 4037	—
Longitudinal	—	107 lbs./in.
Transverse	—	72 lbs./in.
Sealability around Nail	ASTM D 1970	Passed
Low Temperature Flexibility	ASTM D 1970	Passed
Waterproofing Integrity after Low Temperature Flex	ASTM D 1970	Passed
Waterproofing Integrity of Lap	ASTM D 1970	Passed
Thermal Stability	ASTM D 1204	Passed

†All values are approximate.